



SEE MORE. DO MORE.

Specification Sheet

Z-Perform 1000D 2.4 mil Receipt

Features:

- Direct thermal, smooth, uncoated 2.4 mil receipt paper
- Excellent print quality
- Available in white (05610RM)

Suggested Applications:

- General purpose ticketing
- Mobile point of sale receipts
- Work in process tagging
- Archival use

Material Construction:

	Description	Caliper
Facestock	White smooth uncoated direct thermal paper	2.4 mil
Total		2.4 mil +/- 10%

Temperature Performance:

- Minimum Application Temperature: NA
- Service Temperature: -40° F to 140° F (-40° C to 60° C)
- Optimal Storage Conditions: 72° F (22° C) at 50% RH
- Expected Exterior Life: Not recommended for outdoor use

Recommended Tone Settings for Zebra printers using Speed 3, Contrast 0:

	MZ220	MZ320	QL 220 Plus	QL 320 Plus	QL 420 Plus	RW220	RW420
Z-Perform 1000D 2.4mil Receipt	25	25	20	20	20	10	10

Images will remain legible for up to 10 years provided they are formed properly and the receipts are handled and stored under the proper conditions. For archival use these receipts need to be protected from exposure to light, heat, water, solvents, cleaners, plasticizers, and oils (including vegetable oils and skin oils), and they need to be stored with compatible materials at temperatures less than 77°F, and 45-65% RH. Image durability depends on the energy used to print the receipts. To maximize image durability, receipts should be printed at the recommended tone settings.

Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.